

POWER PACK™ MODEL PWR 12-33

POWER PACK™ MODEL PWR 12-33



PORTABLE 12 VOLTS DC POWER WHEN YOU NEED IT.

- High-current output plug for accessory operations (lights, saws, fans, winches, etc.)
- Standard "cigarette lighter" port for running accessories (lights, cell phones, computers, electric tools, etc.)
- Built-in power supply pigtail for easy connection to the PC-100 Controller Unit.
- Built-in harness straps to secure the PC-100 Controller for portability.
- Test button and indicator to show battery state-of-charge.
- Vented carrying case to allow any hydrogen gas exhausted by the battery to safely diffuse without dangerous buildups.
- Charger port only accepts the Power Hawk provided battery charger.
- Shoulder strap for enhanced portability.

Power Hawk is a registered trademark of Curtiss-Wright Flight Systems, Inc.



CURTISS-WRIGHT
POWER HAWK®
RESCUE SYSTEMS



CALL

1-800-PWR-HAWK For more information.

Power Hawk Technologies Inc., 300 Forge Way, Suite 2, Rockaway, NJ07866
Phone: 973-627-4646 · Fax: 973-627-4622 · Website: www.powerhawk.com



POWER PACK™ MODEL PWR12-33



Battery Type: 12 Volts DC - Valve Regulated Lead Acid Battery. Will not leak acid and can be used and stored on its sides.

Battery Capacity: 33 AH

Use on-scene: On average, 8-10 doors and 2 roofs can be removed from vehicles using the P-16 Rescue Tool on one battery charge. This will vary however, according to operator training and technique since battery energy is only being used when the tool is operated.

"Memory" Effect: None. Lead-Acid batteries do not have "memory" problems typical with Nickel-Cadmium batteries.

Charger Required: Use only Automatic Battery Charger(s) provided or recommended by Curtiss-Wright Flight Systems. Other chargers may result in overcharging the battery which will shorten its life.

Recharge Time: Using the provided charger, a fully discharged battery can take up to 15 hours to reach full charge. A partially discharged battery will be less. It is recommended that spare battery packs or other back-up 12 Volts DC power be available.

Battery Life: Approximately 500 recharges (depending on temperature conditions). Charge at least monthly.

Output Ports: 2 high-current, 1 low-current

Weight: 35lbs. (13.2 kg.)

Envelope: 14" x 7" x 15" (35.5 x 17.8 x 38 cm³)